VICTORY GSF-2500 STUMP GRINDER

With E-Starter





GSF-2500 stump grinder with engine

Self propelled stump grinder with powerful 14 hp Vanguard Briggs & Stratton engine and hydraulic drive system for fast removal of interfering roots and tree stumps up to 25 cm deep.



[€] from 3.098

CE

The Victory GSF-2500 stump grinder complies with all safety regulations and is CE tested following the 2006/42/EC machine directive.

Professional stump grinder with hydraulic 2WD

The GSF-2500 stump grinder is powered by an extremely robust Vanguard engine (Briggs&Stratton) with 14hp, that comes with a pullstarter and E-starter system.

1 Stump grinder removes tree stumps and roots from 30cm above ground to 25cm below ground.

2 Hydraulic drive system with two hydraulic motors, one for each 40 cm sized wheel, guarantees easy handling and loading on a trailer over a ramp.

3 Each Greenteeth 700 grinding tooth can be used from three sides, dramatically increasing their durability.

4 Ergonomic, adjustable operator handle for easy operation and transport of the stump grinder.

5 Spare part supply available in the parts section of our online shop

6 Ten pantented, easy replacable and turnable tungstencarbide grinding teeth offer superior performance.

7 The large grinding rotor is 37 cm in diameter and 12 cm in width





Technical Specifications VICTORY GSF-2500 STUMP GRINDER

DATA	GSF-2500
Dimensions (LxWxH)	1850x720x1250 mm
Weight	235 kg
Track width	720 mm
Tire size	4.80/4.00-8 ca. 40 cm diameter
Drive system	2 hydraulic motors - up to 3,5 km/h
Hydraulic tank	10 Ltr.
Recommended hydraulic oil	HLP32 or HLP46
Engine displacement	408ccm; 1cyl. 4 stroke
Performance	14 HP
Starter	pull starter + E-Starter
Fuel tank	6,1 Ltr.
Engine oil / capacity	SAE 10W-30 / 0,95 Ltr.
Fuel consumption	1,5 - 1,8 L/Std. unleaded fuel
RPM	max. 3600 rpm
Grinding rotor drive system	2 drive belts
Grinding rotor size	370 x 120 mm
Number of cutting teeth	10 - 3 times turnable
Cutting teeth	chrom-moly steel with tungsten carbide cutting head / Greenteeth-700 patented
Max. cutting depth	23 mm
Cutting teeth holder	chrome-moly steel
Grinding rotor RPM	max. 2570U/min
Grinding area	below ground: max. 25 cm / above ground: max. 30 cm
Manual cutting sweep width (L-R)	90 cm
Max. working angle allowed	25°
Brake	independant wheel brakes
Housing material strength	2 - 4 mm
Paiting	powder coating, yellow/green
Wooden transport box	172 x 87 x 102 cm



ONLINE-SHOP FOR TRACTOR ATTATCHMENTS

Tiller, Stone Burrier Tillers, Cultivators, Wood Shredders, Wood Chippers Stump Grinder, Trenchers, Shaft Grinder, Wood Splitter and Log Saws



Contact Phone: * 49 (0) 4188 4444 773 E-mail: info@victory-tractor.com

V&B Europe GmbH Am Flidderberg 74 D-21256 Handeloh - Germany